

**Superior technology
for contract cleaning**

Automatic scrubber-driers Mains operated or battery driven: Hakomatic E/B 430



**For quick, economical maintenance cleaning. Wet scrubbing, dry vacuuming
- spotlessly clean in one operation.**

**Hako -
perfect from
product
to service**

Scrubber-driers Hakomatic E/B 430 – maintenance cleaning up to 1.700 m² cleanliness/hour.


The Hakomatic E 430 and B 430 machines are handy, mains operated or battery driven scrubber-driers for quick, economical maintenance cleaning of all types of hard floors. The extremely compact construction and robust machine guarantee a high degree of manoeuvrability, good handling and good visibility. The height adjustable operating handle and the adjustable brush drive (Power-flow) are ideal for fatigue-free operation. Smooth tank and outer surfaces, electric brush change, parabolic squeegee as well as easy access to the machine guarantee low running costs and optimum cleanliness.



All operational switches are within direct view and easy reach of the operator. Operating symbols and working instructions are easy to understand. Excellent view of the area to be cleaned.



Easy tank filling thanks to the large tank opening. Tank can be emptied quickly and easily via the large outlet hose. Overflow protection for the dirty water tank.



The parabolic, floating squeegee makes working close to edges possible and ensures that no water streaks remain even when negotiating corners.



Brushes can be changed quickly without the need for tools – operated at the push of a button directly from the operating handle. Comprehensive range of accessories.

Technical Data Hakomatic		B 430	E 430
Number of brushes	Units	1	1
Brush diameter/working width	cm	43	43
Effective suction width	cm	75	75
Theoretical area performance	m ² /h	1700	1700
Air volume, vacuum	m ³ /h	108	155
Pressure	mbar (mm/H ₂ O)	110 (1100)	200 (2000)
Nominal voltage, frequency	Volt/Hz	24 DC/-	230 AC/50 Hz
Power requirement, total	W	800	1800
Power brush motor	W	450	800
Power suction motor	W	350	1000
Working speed	up to km/h	4	4
Brush revolution	1/min	280	288
Brush pressure	kg/N	20/200	22/220
Specific brush pressure	N/cm ²	0,25-0,35	0,25-0,37
Clean water tank	litres	22	22
Dirty water tank	litres	22	22
Measurements/Weight			
Length, ready for operation	cm	100	100
Width (without/with squeegee)	cm	45/75	45/75
Height, ready for operation	cm	95	95
Total weight, without batteries/brushes	kg	80	76
CE	The Hakomatics E/B 430 fulfil the European regulations with regard to the EC machine guidelines, the EC low voltage guidelines and the EC guidelines with respect to electro-magnetic tolerance. Similarly the machines also comply with the European safety requirements of the standard EN 292 and EN 60 335, as can be recognized from the CE sign which can be found on the machine		
In the interest of technical progress we reserve the right to alter equipment without prior notice.			



DOĞUŞ Tekstil ve Temizlik Makinaları Paz. San. Tic. Ltd. Şti.
 İkitelli OSB Turgut Özal Cad. No: 141 Kat:2
 34303 Başakşehir/İstanbul/Türkiye
 Tel.: +90 212 444 0 764 Fax: +90 212 549 51 49

www.hako.com.tr
www.formula.com.tr
www.dogustemizlik.com.tr

A Member of the Hako Group